



# POLY STUDIO X30 FOR ZOOM ROOMS



# X30



## VIDEO CONFERENCING, MEET RADICAL SIMPLICITY

### **BENEFITS**

- Get any huddle or small room up and running in minutes, with a simple setup process and all-in-one design
- Make it easy for anyone, even guests, to share content wirelessly from any personal device—with no special apps or tools needed
- Powerful audio pickup and incredible noise blocking technology allows every word to be heard without distractions
- On-board support for Zoom means no room PC or Mac is required

### **POLY STUDIO X30**

The Poly Studio X30 video bar delivers radical simplicity in a small, elegant package. In small- and medium-sized rooms, connect to your Zoom meetings with one touch. Experience full boardroom-quality audio, advanced camera capabilities, and quick wireless content—all in one sleek video bar. And say goodbye to unnecessary pucks, cords, and cables, along with the PC or Mac to drive the meeting, since the Zoom Room app is built right in. Easy to install, easy to manage.

- Ideal for huddle to small sized rooms
- Compact, lightweight design easily fits on top or underneath display
- Affordable price delivers excellent huddle room performance without breaking the bank

# **POLY** **STUDIO X30**



## **SPECIFICATIONS**

### **PACKAGE INCLUDES**

- Poly Studio X30
- Cable bundle
- Monitor clamp
- Privacy cover

### **VIDEO INPUT**

- 1x HDMI

### **VIDEO OUT**

- 1x HDMI
- Touch display compatible

### **PEOPLE VIDEO RESOLUTION**

- Supports maximum Zoom people resolution of 1080p @ 30fps (requires 1.8 Mbps)

### **CONTENT VIDEO RESOLUTION**

- Supports maximum Zoom content sharing resolution of 1080p @ 15 fps

### **CONTENT SHARING**

- HDMI Input
- Zoom Wireless Screen Sharing

### **CAMERA**

- 5x digital zoom
- 120° FOV
- UHD 2160p (4K) capture resolution
- Automatic people framing
- Automatic speaker tracking

### **AUDIO INPUT**

- 4x MEMS microphones
- Microphone pickup range up to 15 ft

### **AUDIO OUTPUT**

- Single speaker

### **OTHER INTERFACES**

- 1x USB-A (3.0)
- 1x USB-C

### **AUDIO STANDARDS AND PROTOCOLS**

- Opus
- SILK
- G.722

### **NETWORK**

- IPv4
- IPv6
- 1x 10/100/1G Ethernet
- Auto-MDIX
- Web proxy support
  - Basic
  - Digest
  - NTLM
- Simple Certificate Enrollment Protocol (SCEP)

### **SECURITY**

- Authenticated access to admin menus, web interface, and API
- Local account password policy configuration
- Security profiles
- Local account and login port lockout
- Secure defaults
- Remote logging with support for TLS

### **OPTIONS SOLD SEPARATELY**

- VESA and wall mount kit
- Stand
- Poly TC8
- Poly Trio
- Inverted mount kit

### **INTEROPERABILITY**

- Zoom Certified
- USB device mode

### **ELECTRICAL**

- Auto sensing power supply
- Typical operating voltage/power
  - 37 VA @ 120 V @ 60 Hz
  - 37 VA @ 230 V @ 50/60 Hz
- Typical BTU/h
  - 65

# POLY STUDIO X30



## SPECIFICATIONS

### ENVIRONMENTAL SPECIFICATION

- Operating temperature
  - 0 to 40 °C
- Operating humidity (non-condensing)
  - 15 to 80%
- Non-operating temperature
  - -40 to 70 °C
- Non-operating humidity (non-condensing)
  - 5 to 95%
- Maximum altitude
  - 16,000 ft

### PHYSICAL CHARACTERISTICS

- 17.39 W x 2.46 H x 2.42 D (inches)  
441.8 W x 62.5 H x 61.6 D (mm)
- 1.6 lbs/.73 kg

### LIMITED WARRANTY

- One year Limited Warranty per [www.poly.com/us/en/legal/warranty](http://www.poly.com/us/en/legal/warranty)

---

\*Supported in future software update.

## LEARN MORE

For more information on Poly Studio X30, visit [www.poly.com/studiox](http://www.poly.com/studiox)